

1 3/4" FLANGES (UPSTREAM AND DOWNSTREAM)

"W"

STAR KNOB

AIR FLOW

21 1/2"

2 3/4" HORIZONTAL FLANGES (UPSTREAM) 1 1/2" (DOWNSTREAM)

UPSTREAM FLANGES

HEPA FILTER

LOCKING TRAY

FRONT VIEW

**HEPA SIDE ACCESS HOUSING GASKET SEAL WITHOUT PREFILTER**

**SPECIFICATION**

1. THE HOUSING SHALL BE CONSTRUCTED OF 14 GA GALVANIZED FOR STRUCTURAL REINFORCEMENT. ALL JOINT SHALL BE INTERMITTENTLY DR SEALED WELDED AND SHALL BE FREE OF ALL BURES AND SHARP EDGES. JOINTS SHALL BE SEALED AIRTIGHT WITH SILASTIC CAULKING.
2. THE ACCESS DOOR SHALL HAVE A 1/2" THICK CLOSED-CELL NEOPRENE GASKET AROUND THE INSIDE PERIMETER. STUD AND STAR KNOBS SHALL BE USED TO SECURE THE DOOR.
3. THE STANDARD HOUSING COME WITH A ACCESS DOOR ONE SIDE. STANDARD HOUSING IS A RIGHT HAND ACCESS. THE BUYER MUST SPECIFY LEFT HAND IF REQ'D
4. HOUSING MORE THAN 3 WIDE CONSISTS OF TWO SIDE-BY-SIDE HOUSING IN PARALLEL FILTER REMOVE IS FROM BOTH SIDE OF HOUSING

HOUSING CONFIGURATION	HEIGHT "H"	WIDTH "W"
1 x 1	27 1/4"	24 1/8"
1 x 2	27 1/4"	48 1/8"
1 x 3	27 1/4"	72 1/8"
2 x 1	51 3/4"	24 1/8"
2 x 2	51 3/4"	48 1/8"
2 x 3	51 3/4"	72 1/8"
3 x 1	76 1/4"	24 1/8"
3 x 2	76 1/4"	48 1/8"
3 x 3	76 1/4"	72 1/8"

HOUSING CONFIGURATION \_\_\_\_\_ X \_\_\_\_\_  
 HOUSING DIM: (H) \_\_\_\_\_ (W) \_\_\_\_\_ (D) \_\_\_\_\_  
 HOUSINGS REQUIRED: \_\_\_\_\_

THE DESIGN DENIED AND DESCRIBED HEREON, ENGINEER'S PROPRIETARY INFORMATION, AND ALL RIGHTS RESERVED. THIS DRAWING IS THE PROPERTY OF THE DESIGNER AND IS GRANTED IN WRITING.

UNLESS OTHERWISE SPECIFIED REMOVE ALL BURS AND SHARP EDGES

\*TOLERANCES: DO NOT SCALE  
 XXX ± .0151 Y/X ± 1/16  
 XX ± .03 Z ± .5"

DOBAILING

912 E Washington St. Joliet, IL 60433 Ph (815) 726-4600 Fax (815) 726-8912

**FILTRATION GROUP**

TITLE: HEPA SIDE ACCESS  
 -GASKET SEAL

Part No. \_\_\_\_\_  
 Drawing No. \_\_\_\_\_

RELEASE E.O. \_\_\_\_\_  
 SHEET \_\_\_\_\_