

Dimensions and Performance Data

Model Number	Nominal Size HxWxD	Actual Dimensions HxWxD	No. of Pockets	Rated Air Flow (cfm)
PML 1/1	24 x 24 x 24	23 7/16 x 23 7/16 x 24	8	2000
PML 1/2	24 x 12 x 24	23 7/16 x 11 7/16 x 24	4	1000
PML 5/6	24 x 20 x 24	23 7/16 x 19 7/16 x 24	6	1660

Standard Performance Values and Tolerances

Average Dust Spot Efficiency (ASHRAE 52.1)	90%
Minimum Efficiency Reporting Value (ASHRAE 52.2)	14
Dust Holding Capacity at final pressure drop of 1.5" w.g. (ASHRAE Std Dust)	500 grams
Burst Strength	>12"w.g.
Frame Tolerances	+/- 3/32 inches

Example Item Number: PML 1/1 is 24 x 24 x 24, Gskt Downstream (Back of Header)

Technical Data

	PML 1/1		PML 1/2		PML 5/6	
Air Flow (cfm)	2000	2500	1000	1250	1660	2080
Initial Pressure Drop (" w.g.)	0.43	0.54	0.43	0.54	0.43	0.54
Media Area (sq. ft.)	60		30		45	
Approximate Weight (lbs)	9.3		7.1		4.4	

Specifications

Maximum Temperature	Constant - 160°F Peaks - 200°F
Flammability	UL 900 Class 2
Media	Progressive Density Structure of 100% Synthetic Fibers. Impreganated w/ adhesive for enhanced particle capture and retention.
Relative Humidity	100%
Recommended Final Pressure Drop	1.5" w.g.
Gasket Material	Neoprene
Header Material	Polyurethane
Pocket to Header Attachment	Injection Molded
Pocket Separator	Aerodynamic Flute
Pocket Construction	Ultrasonically Welded

For Sales Only

Customer Name: _____
 Location: _____
 Project: _____
 Item Number: _____



_____ (W) X _____ (H) X _____ 24 _____ (D)

Please Specify Size as Nominal or Exact _____
 Customer Initial and Date for Non-Standard Size _____



Filtrair, Inc.
 600 Railroad Ave
 York, SC 29745

PML Rigid Pocket Filter

90-95% ASHRAE Dust Spot

DR: SVG	Date: 11/19/05	Drawing Number:	Revision:
Page: 1 of 1	SD-PML	0	

YOUR APPROVAL OF THIS PRINT AUTHORIZES FILTRAIR, INC. TO PROCEED WITH MATERIAL PROCUREMENT, TOOLING AND PRODUCT FABRICATION. ANY CHANGES MADE AFTER APPROVAL MAY INCUR FURTHER EXPENSES TO THE CUSTOMER.